Certificate of Location of Government Corner

ID#: 832706 **Description:** 1/4 SEC COR 27 28 83 **Date Set:** 4/17/2012 **County:** Olmsted

Section: 27 **Township:** 108N **Range:** 13W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls 1' west of centerline of north-south township road (50th Ave NE)
The monument is down 0.5'
This corner is located by GPS measurement

Corner History:

5-19-1854 William B. Yerby, Deputy Surveyor, measured north 40.00 chains between Sections 27 and 28. Set quarter section post in mound of earth & sod, deposited charcoal. Made trench with pits and planted Osage Orange seed east & west.

10-25-1893 William Fraser, Deputy County Surveyor, (Book A Pages 536-537, Survey No. 498), Mr. C. Neimers avers that he and Mr. E. Welsh drove a new stake with stone by its side where original government stake stood and now was pile of stones 5' deep, but on direct line of fences east & west and 31' from tree east of stake. Did not dig for corner. Used point in line of fences and 31' from tree east.

11-1-2011 County Survey Crew dug with backhoe to cover lost position and centerline of road and in line with fence west. Found stake located in the center of a group of stones arranged in a triangle pattern down 6.5' in good condition. This portion of roadway is in a fill section so the stake and stones would have been near the surface before the fill was placed. Set 4' telspar pipe with Cast Iron Cap in stake hole in center of the stones down 6.3'. Measured its position using GPS.

4-17-2012 County Survey Crew set 5' telspar pipe with Cast Iron Cap down 0.5' over telspar pipe with Cast Iron Cap.