# Certificate of Location of Government Corner

**ID#:** 832804 **Description:** 1/4 SEC COR 28 33 83 **Date Set:** 6/30/2005 **County:** Olmsted

**Section:** 28 **Township:** 108N **Range:** 13W **Monument Description:** Cast Iron Cap on telspar pipe

**Reference Ties:**

The corner falls 1' north of fence west and in line with willow hedge south
Post w/sign 1' east
This corner is located by GPS reference stations "Ohm F & G"

**Corner History:**

1854 Gov't Notes, William Yerby; 39.98 set quarter section post in mound of earth & sod. Deposited charcoal, made trench with pits and planted osage orange seed N & S. 6.0 stream 5 links wide course NE.

10-1893 W. Fraser Og.536 No.498; Found post at north edge willow hedge avered by P.M. Walker that he set post just east of roriginal gov't stake. Set stone where Mr. Walker avered stake once stood.

3-1973 County Surveyor went to corner area and found 1/16 fence running north. From 27-28-33-34 continued to corner area, hugh willow still runs south with round steel corner post set for fence running west. Badly aged 8" wood corner post with large brace post 8 or 10' south for fence south still in place some 5' east of tree row. Ground frozen 15"±land unbroken, level and little chance of fill. Good chance for stone unless removed to set either of corner posts. Very sharp drainage ravine from 2000' west to level corner area.

6-30-2005 County Surveyor dug to cover area of stone set by W. Fraser in 1893. Found W. Fraser stone 2"x7"x11". Set 6' telspar pipe w/cast iron cap at stone location.