Certificate of Location of Government Corner

ID#: 832805 **Description:** SEC COR 28 29 32 33 83 **Date Set:** 5/19/2006 **County:** Olmsted

Section: 28 **Township:** 108N **Range:** 13W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls 1' west of centerline of N-S twp road and in line with fences east and west
County Survey Disk in N side fence post W 32.52'
This corner is located by GPS references stations "Haney A & B"

Corner History:

1854 Gov't notes, William Yerby; 75.0 small stream 4 links wide course NE. 80.0 set post in mound and deposited charcoal, made trench with pits and planted osage orange seed NW & SE.

10-1893 W.Fraser Pg.536 No.498; Dug and found nothing. Mr. Fred Harvey avers he put his fence running east from this corner exactly east of corner. Set no corner, used fence line for meas. South to set point as 1/4 corner to set center 33.

9-1965 J. Kerr set random line 120D n center road in line fences east and west to hold this careful accurate chainage.

11-1996 County Surveyor found J.Kerr 120d bent and lying down in road. Set 60d at his location as best we could. This lines with fences E & W. It falls 2' west of centerline N-S road on curve.

6-30-2005 County Surveyor dug with backhoe to cover J. Kerr spike location. Found possible mark in much disturbed clay line 6 1/2' deep .7' west and 1.1' south of J. Kerr spike location. Decided to set final corner at J. Kerr location.

5-19-2006 County Surveyor set a 4' telspar w/CIC down 0.4' at J. Kerr's location.