Certificate of Location of Government Corner

ID#: 832905 **Description:** SEC COR 29 30 31 32 83 **Date Set:** 5/27/1976 **County:** Olmsted

Section: 29 **Township:** 108N **Range:** 13W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls on SE side of CP
County Survey Disk in W side 30" Burr Oak SE 94.85'
Center Southerly Gate Post SE 52.6'
NE Corner Shed SW 108'
Post w/sign 1' north
This corner is located by GPS reference stations "Biel & Kitzman"

Corner History:

5-1854 Gov't Notes: William B. Yerby, Deputy Surveyor North between sections 31 and 32. 77.50 chs. Descend a bluff. 80.00 chs. Set post corner to sections 29, 30, 31 & 32 in mound of earth and sod. Deposited charcoal, made trench and pits, planted Osage orange seed N.W. and S.E.

4-1875 Thomas Hunter (P. 268 No. 266), County Surveyor, found mound and pits plain but no stake in the mound.

3-1879 T. Hunter (P. 355 No. 347) found a fence post in the mound described P. 268.

5-1976 County Surveyor dug around the corner post (mainly East side) but did not find anything.

5-27-1976 County Surveyor accepted the corner post as the corner. Set a C.I.M. over a 3/4" x 3' conduit on the S.E. side of the corner post as the corner.

6-16-1997 County Surveyor found CIM in good condition, sign and post 0.8' north.

12-17-1997 McGhie & Betts found C.I.M. in place and took two additional ties. Fence south gone.

7-5-2005 County Surveyor found CIM at surface in good condition.