Certificate of Location of Government Corner

ID#: 832906 **Description:** 1/4 SEC COR 29 30 83 **Date Set:** 5/26/1976 **County:** Olmsted

Section: 29 **Township:** 108N **Range:** 13W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 35' west of centerline of north-south township road (30th Ave NE) on curve
The monument is down 0.2'
SE corner (main block) foundation NW 171.60'
Chisel "+" in west end concrete culvert NNE 35.10'
Center 4" Cedar W 19.8'
County Survey Disc in N side PP #34831 W 63.33'
Post w/sign 2' west
This corner is located by GPS reference stations "O'Marro A & B"

Corner History:

5-23-1854 William B. Yerby, Deputy Surveyor, measured 40.00 chains north between Sections 29 and 30. Set a post in mound, deposited charcoal, made trench and pits, planted Osage Orange seed east and west.

4-14-1875 Thomas Hunter, County Surveyor, (Book A, Page 268, Survey No. 266), 1/4 post missing and could not be found by digging. Set 4"x10"x14" stone midway and on line.

3-25-1879 Thomas Hunter, County Surveyor, (Book A, Page 355, Survey No. 347), could not find stone. Set temporary stake midway and on line.

5-7-1976 County Survey Crew dug and found small pieces of stone down 2' with black mark beneath extending 8" into clean clay.

5-26-1976 Roger Brand, County Surveyor, accepted mark as location of Thomas Hunter's 1875 corner. County Survey Crew set Cast Iron Monumnet over pipe at this location. RPs -SE corner (main block) foundation NW 171.60', Chisel "+" in west end concrete culvert NNE 35.10', Center 4" cedar W 19.8', County Survey Disc in north side Power Pole #34831 W 63.33'.

7-5-2005 County Survey Crew found Cast Iron Monument down 0.2' in good condition. Set post w/sign 2' west. Set reference stations "O'Marro A & B" and measured their positions using GPS.