# Certificate of Location of Government Corner

**ID#:** 833005 **Description:** W SEC COR 30 31 83 **Date Set:** 6/12/1980 **County:** Olmsted

**Section:** 30 **Township:** 108N **Range:** 13W **Monument Description:** Cast Iron Monument

**Reference Ties:**

County Survey Disk in N side 18" twin Burr Oak (up 3') E 16.83'
County Survey Disk in W side 18" Burr Oak SW 27.57'
Post w/sign 2' south
This corner is located by GPS reference stations "Lind A & B"

**Corner History:**

10-1853 Gov't Notes John Ball, Deputy Surveyor North between sections 31 and 36. 80.00 chs. Set post for corner to sections 25,30, 31, 36. Burr Oak 10 in. S36°W 200 lks. Burr Oak 10 in. N55°W 310 lks. Dug trench per instructions.

5-1863 P.C. Compton, County Surveyor (Book A, Page 69, No. 98) used this corner to set the 1/16 West and North midway and the 1/16 East at proportionate Gov't measure.

3-1879 Thomas Hunter, County Surveyor, (Book A, Page 355, No. 347 and Old Field Book 5, Page 95) states "Section corner gone, but found the S.W. witness tree standing which by the field notes places the corner at the corner of fences which is claimled to have been set when the original section corner stood. --Set no stake." He used the corner to set a temporary stake on line and at proportionate Gov't measure at the 1/16 East and to set a temporaty stake on line and at proportionate Gov't measure at the 1/16 East and to set the 1/16 North (no description) midway and on line.

7-1917 John Kerr, Deputy County Surveyor, (Book B, Page 268 and Kerr Book -10, Page 17) found stone after much search 17' West of Burr Oak tree used as fence corner.

5-1967 John Kerr, County Surveyor, (Kerr Book 93, Pages 50-53, card, and Cert. filed) found limestone. Set a C.I.M. over a 1-1/4" pipe on bedrock.

5-9-1980 County Surveyor dug out Kerr's C.I.M. to verify corner. Found the C.I.M. packed in small pieces of limestone and over a 1-1/4"x9" piece of pipe standing on bedrock. There was a 1-1/2"x5-1/2"x12" limestone standing on the East side of the C.I.M. which was the only stone which could have been the stone found by Kerr. Also found a 2" to 2-1/2" hole starting 1' deep and running down 14" to rock and filled with wood fragments 1.2' West of the C.I.M. which appeared to be the remains of a stake driven to bedrock. Set the C.I.M. which appeared to be the remains of a stake driven to bedrock. Set the C.I.M. back at the same location Kerr had it.

6-12-1980 County Surveyor cut into the face of a Burr Oak that could possibly be the S.W. Gov't bearing tree. Found the Gov't blaze with scribing plain. This tree S35°W (Magnetic Bearing) 130.9' from the C.I.M. Accepted Kerr's C.I.M. as the corner.

6-16-1980 County Surveyor set a survey marker sign and post 2' North of the C.I.M. and took references.

9-27-2005 County Surveyor found CIM in good condition down 0.1'. Updated tie but did not check them. Reset sign & post south.