Certificate of Location of Government Corner

ID#: 833006 **Description:** W 1/4 SEC COR 30 83 **Date Set:** 12/1/75 **County:** Olmsted

Section: 30 **Township:** 108N **Range:** 13W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 46' west of centerline of residential driveway on curve
Post w/sign 2' west
This corner is located by GPS measurement

Corner History:

10-1853 Gov't Notes; 40.0 set post for 1/4 section corner. RPs- 14" burr oak N 4 1/2E 370, 6" burr oak N°30'W 372.

5-1879 T. Hunter Pg.355 No.347; found stone set by adjacent land owners. 16 south,east, and 16 center SW 1/4 30 set stake.

5-1967 J. Kerr found stone and stake remains. Set CIM with 1/2"x2' pipe below stone. RPs- Corner lies in line fence south, 2' north fence west, Cross cut in top large boulder (2' x 3' + -) west northwest, 18.0' , Co. Surv. Disc in 10' high post on E. side of fence to So. E.S.E. -24.88', Co. Surv. Disc in 9" most easterly of twin blazed Boxelder Tree - N.E. 57.0'.

12-1-1975 County Surveyor found Kerr's CIM 2.2' deep. Set CIM over and up to surface. Corner in line with fence south and 2' north of fence west. RPs- CSD east side of 10' post on east side of fence south ESE 24.88', spike & CSD in 9" most easterly of twin blazed boxelder NE 57.0', cross in large boulder WNW 18.0'.

9-27-2005 County Surveyor found CIM in good condition down 0.5'. All ties are gone and both fences gone. Set sign & post 2.0' west.