Certificate of Location of Government Corner

ID#: 833206 **Description:** 1/4 SEC COR 31 32 83 **Date Set:** 5/20/1997 **County:** Olmsted

Section: 32 **Township:** 108N **Range:** 13W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls 1' south of E-W fence
30d spike in quadruple 15" Boxelder W 177.6'
30d spike in triple 18" Boxelder ESE 7.16'
Post w/sign 1' north
This corner is located by GPS reference stations "K.S. I & II"

Corner History:

5-1854 Set by William Yerby 2.00 to top of bluff from corner. 4.50 descend a same bluff. 10.00 to foot of same bluff. Enter dry bottom E&W. 20.00 leave bottom E&W and ascend a bluff. 25.00 to top of same bluff. 40.00 Set a quarter section post in mound of earth and sod deposited charcoal. Made trench and pits, planted osage orange seed E&W.

5-20-1997 County Surveyor dug at Hunter's measure from 1/16 fence post E and in fence line. Dug hole 3' W-S-E and 4' N. of computed position. Dug down 3' to clean clay. At 1' down found stones and boulders lying flat West and SW of fence post. 1 1/2' down fence. First signs of old fence post mentioned by Hunter. Post ran down to clay. Set 5' telspar W/CIC at fence post location.

12-17-1997 McGhie & Betts found monument in place and took additional references.

9-13-2011 County survey crew found cast iron cap in good condition