Certificate of Location of Government Corner

ID#: 833304 **Description:** S 1/4 SEC COR 33 83 **Date Set:** 9/8/2011 **County:** Olmsted

Section: 33 **Township:** 108N **Range:** 13W **Monument Description:** 1" sq. pipe with cap 42638

Reference Ties:

The monument is at the surface.
The monument is 9' south of centerline of east-west road.
This corner is located by GPS reference stations "Foxy A & B"

Corner History:

1853 John Ball; 40.0 set post and drove charred stake for 1/4 section corner. Built mound with trench, and planted SE osage orange and NE appleseed. RPs- 5.0 enter aspen grove bears SW, 7.50 leave same bears SW.

10-25-1893 W.Fraser Pg.536 No.498; Corner couldn't be found. A Mr. White avers he set NW corner cemetery fence where stake for cemetery stood which was exactly 33' south of 1/4 corner when it was standing. Drove stake at that point. Meas. East 40.02 to section corner which was set midway on range line to S 1/4 34.

4-6-1911 C.Larson Book B, Pg.150; used fence of cemetery running south as E-W line. Meas. East 40.0, set stake M & L.

5-20-2005 County Surveyor searched for but did not find any monument. County Surveyor then computed a coordinate position in line with cemetery fence south and on line from southeast corner of Section 34 to southwest corner of section 34. The computed location checks with the measurement to the back line of the cemetery.

9-8-2011 County survey crew set 1" square pipe with cap using the coordinate position computed in 2005.