Certificate of Location of Government Corner

ID#: 833305 **Description:** S SEC COR 32 33 83 **Date Set:** 6/8/2000 **County:** Olmsted

Section: 33 **Township:** 108N **Range:** 13W **Monument Description:** 1" square pipe w/cap RLS #15809

Reference Ties:

The corner falls 2' north of centerline of CSAH 14 and 3' west of centerline of twp road north
SE corner old Ringe Creamery NW 57.80'
120d spike in NW side 14" Green Ash NE 70.15'
Bolt in top concrete pillar 18" square up 24" SE 73.67'
County highway disk in NE side PP SE 71.35'
Ref pipe SSW 35.41'
This corner is located by GPS measurement

Corner History:

10-1853 By John Ball, 80.00 set post for corner to sections 4,5, 33&32. Burr Oak 20 S55E 130 lks. Burr Oak 18 N50W 544 lks. & dug trench per instructions planted SE Osage Orange NE Apple.

3-1898 W. Fraser P.620 No.563 S5, found stone as corner. 16 south set stake and long stone on line at 21.11'. 1393.26' then 20.09' to 1/4 stone set. Measure west 39.80 to stake found, stone set.

1936 county highway department found original recorded stone, corner long used by road and private surveys, measure west 5260.4'. RPs- spike in 12" ash NE 49.5', spike in 30" maple SE 43.9', SE corner creamery foundation NW 57.8'.

1941 RP by Kolb; bolt in top of conc. Block SE 73.6', disc in ash tree NE 70.5'.

10-1965 J. Kerr, dug in blacktop from references, found 60d down 18" corner either deep or gone. Set CIM over 5/8"x10" rod bottom rod would be 3' no stone. SE corner old ringe creamery bldg. NW 57.8'. 120d NW side 14" green ash up 10" NE 70.15'. Bolt on top concrete pillar 18" square up 24" SE 73.67'. Disc on NE side power pole SE 71.35'.

11-5-1970 County Surveyor, run and measure line west set S1/432 on direct line inters by line from 107.13' over. Measure W 2624.12' to S1/4 32 then 2628.43' to SW 32.

9-22-1976 County Surveyor dug with backhoe and found CIM to be over 2 stones. One stone 21/2"x5"x10", the other 4"x7" extending into clay. Stones 31/2' deep.

9-23-1976 County Surveyor set CIM over 1 1/4"x20" light pipe back at John Kerr's location. Corner 1'E of fence S, 3' N centerline E-W road, 3'W centerline road N. RPs- SE corner old Ringe Creamery NW 57.80', 120d on NW side 14" green ash NE 70.15', bolt on top conc pillar 18" square up 24" SE 73.67', disc on NE side of pp SE 71.35'.

11-27-1996 County Surveyor found CIM in good condition 4" deep in blacktop CR #14.

6-14-1999 County Surveyor found CIM down 0.4'. Set ref pipe and tied out corner.

6-8-2000 County Surveyor set 1" square pipe w/cap at surface from 1999 tie out.

5-20-2005 County Surveyor found 1" square pipe w/cap at surface in good condition.