Certificate of Location of Government Corner

ID#: 833505 **Description:** S SEC COR 34 35 83 **Date Set:** 11/14/1964 **County:** Olmsted

Section: 35 **Township:** 108N **Range:** 13W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 11' south of centerline of twp road east and in line with fence south
County highway disk in PP NE 57.67'
This corner is located by GPS measurement

Corner History:

1853 Gov't Notes, John Ball; 60.0 leave openings & enter Prairie bears NE, 69.20 brook 3 links wide bears NE, 80.0 set post and drove charred stake. Built mound with trench and planted osage orange seed SE and apple seed NE.

5-1873 T. Hunter Pg.223 No.226; found remains of oak bark & rotton wood. Set new stake. 16 south, west, and center NE 1/4 3 set new stake.

11-1877 T. Hunter Pg.324 No.318; found stake.

10-1946 J.Kerr shows cedar post with limestone on SE side. RPs- S31.75 nail tele pole, SE 50.2' 2nd steel post east of corner post, NE 43.2' wood plug on bank.

11-14-1964 J. Kerr found the south common corner Sections 34 and 35 Farmington Township which was evidenced by an iron monument and a wood hub. Placed a cast iron monument over iron rod. RPs- disc in pp NE 57.67', corner lies in direct line fence south and on south edge traveled road.

6-13-1983 County Surveyor found CIM and iron ok. Old RPs- not right. Took new RPs- county highway department disc in SE side pp NE 57.67', county highway department disc in w side cut off tele pole S 36.51'.

10-27-2005 County Surveyor found CIM in good condition down 0.8'. Disc in PP to the NE still there, did not recheck, PP to the south gone.