Certificate of Location of Government Corner

ID#: 833604 **Description:** S 1/4 SEC COR 36 83 **Date Set:** 4/8/2008 **County:** Olmsted

Section: 36 **Township:** 108N **Range:** 13W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 4' north of centerline of E-W twp road, 2' west of fence row south and 60' east of centerline of farm entrance north County highway disk in N side PP #24385 ESE 183.4'

Corner History:

10-1853 John Ball, 40.00 set post for 1/4 section corner. Burr Oak 10 N56W 120 lks. Burr Oak 14 S21W 325 lks.

5-1872 T. Hunter, P.202, No.211 found short stake in ground. Measure east and west 39.85'

11-1886 T. Hunter, P.416, No.405 found iron rod and stone in road set by A. Raymond after survey P.202, tested NW bearing tree still standing. 16 west set stake M&L 19.97 with many woodlot corners north of above 1/16 corner.

5-1898 W. Fraser, P.639, No.575 found corner described P.416. 16 west set stake M&L 19.95.
16 center SW1/4 36 set stone M&L 19.95 N-S 1/16 line.

6-22-1966 J.Kerr, dug very extensively 5'x7' to clay. Found stone and iron bolt. Set CIM over iron bolt with stone and glass at base of monument. Corner lies 2.6' west fence south. Corner lies 4.0' north centerline traveled road. Center 30" Burr Oak with large deep blaze toward Cor. NW. Disc North side power pole ESE 183.5'. Road fence on south side of road.

4-3-2008 County Surveyor found CIM down 2.6' in good condition.

4-8-2008 County Surveyor found CIM down 2.6' in good condition. Set CIM over CIM down 0.5'.