Certificate of Location of Government Corner

ID#: 840206 **Description:** 1/4 SEC COR 2 3 84 **Date Set:** 5/9/2007 **County:** Olmsted

Section: 02 **Township:** 108N **Range:** 14W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls 1' NE of CP to fences west and south
Old stone with cross set as witness NE 1.93'
County Survey Disk in S side 18" Oak ENE 32.55'
This corner is located by GPS reference stations "Ritter B & C"

Corner History:

1854 Gov't Notes, M.Karrick; 40.0 set 1/4 section post. RPs- 20" white oak N39 W40, 24" white oak N85 E115.

12-1895 W.Fraser Pg.586 No.534; Corner gone, no evidence could be found. Set large limestone on section line and gov't proportion. 16 south, east, and north set stake.

1960 McGhie found stone.

8-11-1966 J. Kerr found 12" x 18" x 36" limestone with +. Set CIM over 5/8"x12" rod. Cross on stone now 1.58' NE of CIM. RPs- 20D east side 22" red oak S 9.0, corner lies 2' south, 1' east of old fence corner post.

9-1972 County Surveyor found CIM in good condition.

6-21-2004 County Surveyor found CIM up 0.5' leaning northwesterly. Removed and found 5/8" rod laying flat. Put rod at CIM location.

11-3-2005 County Surveyor found rerod up 0.1' in good condition. Found old stone NE but did not fit with ties in the notes. Turned angle from "Ritter A&B" to cross on stone.

5-9-2007 County Surveyor found 1/2" x 2.1' rod up 0.2' in good condition, took local ties and removed. Found 5/8" x 12" rod down 1.4' in good condition, stone was 1.94' NE. Set 5' telspar w/CIC up 0.2' at 5/8" rod location which was accepted as final location. CSD w/concrete nail in S side of 18" Oak ENE 32.55'. Cross in stone NE 1.93'.