Certificate of Location of Government Corner

ID#: 840209 **Description:** SEC CEN 2 84 **Date Set:** 5/26/1925 **County:** Olmsted

Section: 02 **Township:** 108N **Range:** 14W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.

County Surveyor recommends using the monumented center of section.

5/8" rod

Reference Ties:

The corner falls in line with fences north, east, and west
The monument is up 0.1'
This corner is located by GPS reference stations "Deer Bait B & C"

Corner History:

12-9-1895 William Fraser, County Surveyor, (Book A, Pages 586-588, Survey No. 534) set iron stake with pile of stones around it at intersecting quarter lines. 1/16th South set stake midway and on line at 20.04 chains (1322.64') to South 1/4. 1/16th West set iron stake midway and on line at 19.73 chains (1302.18') to West 1/4. 1/16th Center of SW 1/4 set stake at intersecting sixteenth lines.

5-26-1925 John Kerr, County Surveyor, (Kerr Field Book #-6, Page 12) set or found 5/8" rod. The corner falls on SE side 2" pipe corner post to fences north, east, and west.

7-17-1963 John Kerr, County Surveyor, found 5/8" steel rod.

9-14-1989 Tom Ferguson used computed center at intersecting quarter lines.

5-29-1997 GGG used shows center of section but does not indicate how it is computed.

9-20-1997 GGG used 1/2" rod position.

6-11-1998 GGG used 1/2" rod position.

4-6-1999 GGG used 1/2" rod position.

11-29-2000 GGG used 1/2" rod position.

2-12-2002 McGhie & Betts, Inc. used computed center at intersecting quarter lines for the plat of Zumbro Haven.

11-18-2003 Vince Fangman used 1/2" rod position.

5-26-2005 Fangman Land Surveying found and used 1/2" rod. He notes that 1/2" rod falls 1.04' north and 0.60' east of computed center at intersecting quarter lines.

10-17-2005 County Survey Crew found 1/2" rod up 0.1' in good condition and measured its position using GPS.

9-20-2011 Joel Thoreson, County Surveyor, recommends using the monumented center of section based on historical use of this position.

9-22-2011 Fangman Land Surveying used computed center at intersecting quarter lines.

5-29-2019 Zillgitt Civil Design found and used monument.