Certificate of Location of Government Corner

ID#: 840307 **Description:** N SEC COR 3 4 84 **Date Set:** 9/22/72 **County:** Olmsted

Section: 03 **Township:** 108N **Range:** 14W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 20' west of CP to fences west and south
60d nail in E side large Oak SSW 44.6'
60d nail in NE side large Oak SSE 15.7'
This corner is located by GPS reference stations "Smars A & B"

Corner History:

1854 Gov't Notes, M.Karrick; 80.60 Intersect Parallel No.2 980 links east 1/4 section post in south boundary at section 33 T109. RPs-7" jack oak S61 W195, 10" burr oak S51 E370.

6-1891 T. Fraser (unrecorded survey) pg. 95 field book. Found a marked stake set by Mr. Goldberg in place of the original stake.

12-1895 W. Fraser Bk. A pg. 586. Found the stake and meas. E. 10451.76'.

9-22-1972 County Surveyor after an extensive study of Sec. 2 & 3 reset this corner with a 5/8" by 2' rod with a Cast Iron Monument over the top and a sign post next to the monument. RPs-60d nail on the E. side of a large Oak S.S.W. 44.6'. 60d nail on the N.E. side of a large Oak S.S.E. 15.7'. 3/4" pipe set as the S. 1/4 Cor. Sec 33 Wabasha C. W. 646.8'.

4-11-1983 County Surveyor found C.I.M. and RP's ok. Corner 20' West of fence corner to fences West and South.

6-18-2004 County Surveyor found CIM at surface in good condition.