# Certificate of Location of Government Corner

**ID#:** 840407 **Description:** N SEC COR 4 5 84 **Date Set:** 4/19/1983 **County:** Olmsted

**Section:** 04 **Township:** 108N **Range:** 14W **Monument Description:** Cast Iron Cap on telspar pipe

**Reference Ties:**

The corner falls 2' west of N-S fence
Pop cap in W side CP NNE 11.85'
Post w/sign 2' East
This corner is located by GPS reference stations "Prokasky A & B"

**Corner History:**

1854 Gov't Notes: Michael Karrick, Deputy Surveyor North on true line between Sections 4 and 5. 40.00 chs. Set quarter section post in mound with trench, pits, charred stake and Osage Orange seeds N.E. & S.W. 80.28 chs. Intersected standard parallel No. 2 970 lks. East of quarter section post on South boundary of Section 32 in township 109 North of range 14 West 5th principle meridian and set post for corner to Sections 4 and 5. Erected mound with trench, pits, and Osage Orange seeds at each angle.

6-1891 Thomas Fraser, County Surveyor, (Old Fieldbook 7, Pages 95-98) measured from N. Sec. Cor. 4-5 (no description) 79.15 chs. East to N. Sec. Cor. 3-4 (a marked stake) to set the N. 1/4 Cor. 4, probably midway and on line. Measured 40.37 chs. South to 1/2 Cor. 4-5 (no description) then 40.09 chs. To Sec. Cor. 4-5-8-9.

9-1893 William Fraser, Deputy County Surveyor, (Book A, Page 533, No. 496) found "casting" at this corner. He measured West to the N.W. Cor. 6 to set N. Sec. Cor. 5-6 on line and according to Gov't measure. (meas 80.175 West, then 78.385 chs. To N.W. 6).

6-1894 William Fraser, Deputy County Surveyor, (Book A, Page 550, No. 508) found stone and stake. Drove iron stake in its place. He used this corner to set the 1/16 South, a stone, on line and at prorated Gov't measure to 1/4 Cor. 4-5, a long limestone, set on line and at prorated Gov't measure to Sec. Cor. 4-5-8-9. (meas. South 20.30 chs. To 1/16, then 20.02 chs. To 1/4 Cor. 4-5, then 40.04 chs. To Sec. Cor. 4-5-8-9). He also set the 1/16 West, a stone and stake, midway (20.04 & 5/16 chs.) and on line to the N. 1/4 Cor. 5, an iron stake 3' long, set midway (40.04 & 5/8 chs.) to N. Sec. Cor. 5-6 set in survey No. 496.

4-1910 John Rafter, Surveyor, (letter to Thomas Fraser) measured 9.70 chs. From the N-S fence at N. Sec. Cor. 4-5 to a "fence post marked for Std. 1/4 Cor. Sec. 32".

6-5-1969 John Kerr, County Surveyor, (Kerr Book 98, Page 63) found 1" shaft with gear on top 11 ft. South of fence corner and 2.7 West of N-S fence. Measured 2661.6 South to 1/4 Cor. 4-5 (found) then 2641.5 to Sec. Cor. 4-5-8-9 (found). Also found stone 1323.4 West at the 1/16 West and found the mark of Fraser's iron rod at the N. 1/4 Cor. 5 1323.2 West of said 1/16th.

4-19-1983 County Surveyor found shaft found here by Kerr. Removed shaft and set a telspar pipe with a cast iron cap in its place. RP-pop cap in west side of corner post NNE 11.85. Found a 1" iron 640.22 West at the South 1/4 Cor. 32 but could not find the Gov't corner there. Measured East to the N. Sec. Cor. 3-4.

10-1-2002 County Surveyor found cast iron cap on telspar pipe down 0.2' in good condition. Point falls 2.0' West of fence running N-S. Set sign and post 2.0' East.