Certificate of Location of Government Corner

ID#: 840504 **Description:** 1/4 SEC COR 5 8 84 **Date Set:** 5/28/69 **County:** Olmsted

Section: 05 **Township:** 108N **Range:** 14W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls in centerline of N-S twp road
Nail & disc in PP #37518 SSE 130.5'
Nail & disc in PP #37519 NNE 126.0'
This corner is located by GPS measurement

Corner History:

1854 Gov't Notes, M.Karrick; 40.0 set temp. 1/4 section post west on true line between sections 5-8. 40.0 set 1/4 section post in mound with trench, pits, charred stake, and osage orange seeds NE & SW.

5-1892 T.Fraser Pg.485 No.462; Found stone 4"x4"x16". 16 south, and west set stone.

5-1894 W.Fraser Pg.550 No.508; Found corner. 16 east,north, and center SE 1/4 5 set stone.

5-28-1969 J. Kerr found limestone as recorded. Set CIM over original stone, iron bar, glass, and cans. RPs- coke cap in pp# 37518 SSE 130.5, Mountain Dew cap in pp# 37519 NNE 126.0, corner lies near exact center road some 3' north very shabby fence west.

10-1977 County Surveyor found T.Fraser 26x22x15 stone on NW side corner post and 1.8 deep with notch or drill hole in top side. Corner 1.6N and 3.3 W of traverse nail.

9-30-2002 County Surveyor found CIM down 1' in good condition.

11-7-2011 Mike Hendrickson, MNDOT Crew Chief, found CIM down 1' in good condition. Set 3 new reference ties as follows: Nail and brass disk on east side of fence post, up 2.5', West 41.45 feet. Resistor on west side of power pole #44708, up 2.5', Northeast, 181.67'. Resistor on east side of power pole #44469, Southeast, 128.86 feet.