Certificate of Location of Government Corner

ID#: 840505 **Description:** SEC COR 5 6 7 8 84 **Date Set:** 6/3/1969 **County:** Olmsted

Section: 05 **Township:** 108N **Range:** 14W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls under N-S fence
Orange pop cap in red cedar post N 19.7'
Sign on wood fence post 2' south
This corner is located by GPS measurement

Corner History:

1854 Gov't Notes: M. Karrick; 80.0 set post for corner to sections 5-6-7-8. Erected mound with trench, pits, charred stake, and osage orange seeds at each angle.

5-1892 Thomas Fraser Pg.485 No.462; Found stake in center pile of stones. Set stone in its place with cross on cap at 1/4 6-7. 16 east set boulders, 16 south set stone.

9-1893 W. Fraser Pg.550 No.508; Found iron in pile of stones.

6-1894 W. Fraser Pg.550 No.508; Found corner. Set 1/16 north.

6-3-1969 J. Kerr set CIM over original stones concrete, glass, and cans. RPs- fence line running east 6', orange pop cap in red cedar post N 19.7, corner lies under fence running north.

10-1-2002 County Surveyor found CIM down 0.4' in good condition. Set sign on wooden fence post.

2-26-2010 Rudy Martin, MN/DOT Crew Chief, found CIM in good condition.

11-8-2011 Mike Hendrickson, MNDOT Crew Chief, found CIM in good condition. Set one additional reference tie as follows: Nail and blue disk in east side of power pole, up 1', West, 1136.13' feet.