Certificate of Location of Government Corner

ID#: 840506 **Description:** 1/4 SEC COR 5 6 84 **Date Set:** 6/4/69 **County:** Olmsted

Section: 05 **Township:** 108N **Range:** 14W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 2' south of centerline of E-W twp road and 1' west of fences N-S
Nail & disc in CP N 38.25'
Nail & disc in PP NE 117.25'
This corner is located by GPS measurement

Corner History:

1854 Gov't Notes,M.Karrick; 40.0 set 1/4 section post in mound with trench, pits, charred stake, and osage orange seeds NE & SW.

5-1893 W.Fraser Pg.533 No.496; Couldn't find corner.

6-1894 W.Fraser Pg.550 No.508; Couldn't find corner. Relocated it on line and gov't prop. Measure. Set boulder & stake. 16 south, east, and west set stone.

6-4-1969 J. Kerr set CIM over 1x10 pipe in depression of stone with narrow tooth wedged in ring of boulders around pipe and glass. Pepsi cap in pp ENE 117.25'. RPs- 38.15 N to pepsi cap in pp.

6-5-1998 County Surveyor found CIM in good condition 10" deep in crushed rock.

6-7-1999 County Surveyor found CIM down 1.0' in good condition.

10-1-2002 County Surveyor found CIM down 1.0' in good condition.

2-26-2010 Rudy Martin, MN/DOT Crew Chief, found CIM in good condition.