Certificate of Location of Government Corner

ID#: 840804 **Description:** 1/4 SEC COR 8 17 84 **Date Set:** 5/26/69 **County:** Olmsted

Section: 08 **Township:** 108N **Range:** 14W **Monument Description:** Cast Iron Monument

Reference Ties:

Nail and disk up 2' in 36" Red Oak, Southeast, 20.9'
Post w/sign 2' East
This corner is located by GPS reference stations "Moto A & B"

Corner History:

1854 Gov't Notes,M. Karrick; 40.0 set temp 1/4 section post west on true line between section 8 & 17. 40.0 set 1/4 section post in mound with trench, pits, charred stake and osage orange seeds NE & SW.

5-1892 T.Fraser Og.485 No.462; Found mound, but no stake. Set stone 7x7x13 at inters of projected lines. 16 north set stone.

4-1904 W.Fraser Pg.76B S 17; found stake and stone.

1952 McGhie found limestone with cross. RPs- spike 15" oak NE 28.05, spike oak SE 25.0, spike 12" oak S 1.5, NE corner outlot 10 S 92.5.

1966 or 1967 J. Kerr found McGhie's RPs.

5-26-1969 J. Kerr found limestone with + in top as recorded. Placed 5/8"x9" bolt with nut on bolt CIM with original stone with cross on east side 10" below top of CIM. Glass and many large limerock lying flat around top of CIM. RPs-North to spike in 12" Burr Oak 10.4 feet. South to spike in 14" Burr Oak 24.5 feet. South of East spike in 24" red oak 21.6 feet. North Northeast spike in 30" red oak 26.0 feet.

6-21-2001 County Surveyor found CIM down 0.4' in good condition. Set post w/sign 2' E.

1-27-2003 Mn/DOT Survey Crew found monument in good condition.

11-7-2011 Mike Hendrickson, MNDOT Crew Chief, found CIM down 0.2' in good condition. Set 2 additional reference ties as follows: Nail and blue disk in 8" ash tree, up 1', North, 2.6'. Nail and blue disk in 6" ash tree up 1', South, 9.3 feet.