Certificate of Location of Government Corner

ID#: 841009 **Description:** SEC CEN 10 84 **Date Set:** 10/8/2004 **County:** Olmsted

Section: 10 **Township:** 108N **Range:** 14W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.
Mag Nail

Reference Ties:

The corner falls 1' south of centerline of CSAH 12 and 5' east of centerline of twp road north
This corner is located by GPS reference stations "Closner A & Clifford A"

Corner History:

5-16-1892 T.Fraser Pg.484 No.461 S 10; Used corner. Set temp point south. Set points east, set boulder 10x12016 at 17.46 then 22.46 to E 1/4 10.

6-1902 W.Fraser Pg.42B S10; Planted stone. Meas. North. 16 east, west, south, set stone.

1939 Bk.113 Pg.77; Indicates a rotted stake in earlier survey and ties taken; Disc tele pole NE 24.0, spike in pp NNW 56.9, disc pp S 84.0, meas. North to S 1/4 3 2627.7, spike on tele pole north 300± a 1941 bench mark.

5-1970 County Surveyor set 5/8" rod as corner.

8-26-1971 P.E. Highum found and used monument.

9-1972 County Surveyor found 5/8" rod. Reset center 10 and drove RR spike flush in blacktop.

5-1975 County Surveyor found 1/4 9-10 1.6' north, therefore center must move 0.8' north.

7-1-1982 Thomas Taylor Co. found and used monument

2-7-2001 County Surveyor found nothing.

10-8-2004 V. Fangman set a mag nail at center of section 10 at intersecting quarter lines.

3-15-2005 V. Fangman used computed center at intersecting quarter lines.

3-7-2006 County Surveyor found mag nail at surface in good condition.