Certificate of Location of Government Corner

ID#: 841105 **Description:** SEC COR 10 11 14 15 84 **Date Set:** 6/14/2004 **County:** Olmsted

Section: 11 **Township:** 108N **Range:** 14W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls in centerline of E-W twp road and 3 1/2' west of centerline of twp road south
Nail & disc in PP #37882 SE 52.34'
Nail & disc in PP #37881 SW 35.56'
Nail & disc in TP NW 35.49'
This corner is located by GPS measurement

Corner History:

1854 Gov't Notes, M.Karrick; 80.0 set post for corner to section 10-11-14-15. RPs- 6" jack oak S 59 W130, 7" jack oak N49 W42, 6" jack oak N43 E46, 6" jack oak S49 E39.

5-1892 T.Fraser Pg.484 No.461; Found stake with stones around it. Found black oak as NW bearing tree

5-1900 C.Armstrong Pg.668 No.594; Found sandstone broken. Set burr oak stake with small stones around it. 16 north set sandstone, 16 center SW 1q/4 11 set stone.

6-1902 W.Fraser Pg.42B; found stake & broken stones. Set new stake and stone.

1916 Power Dam Survey found stone.

5-1941 J.Kerr Bk.23 Pg.?; Power Dam Survey. 1" pipe with 1/2" pipe riser, 3/4" pipe in road bank SW 21.65, center 5" ash tree SE 23.0.

6-1947 J.Kerr Bk.34 Pg.13; Found 3/4" pipe. RPs- 60D in 30" burr oak WNW 186.0, spike in pp SE 52.4.

5-19-1969 J.Kerr found iron pipe over boulder stone as recorded. Set CIM with nothing below but original stone. RPs- Corner lies center line E-W road, corner lies 3 1/2' east to center road south, corner lies 2 1/2' west to edge road south, pepsi cap tele pole brace NW 35.5, coke cap pp# 37881 SW 35.5, pepsi cap pp# 37882 SE 52.4.

6-14-2004 County Surveyor found CIM with head broken off down 1.3' in good condition. Took local ties and removed. Probed down another 1 1/2' and stone was still there. Set 21" CIM down 0.4' from local ties.