Certificate of Location of Government Corner

ID#: 841304 **Description:** 1/4 SEC COR 13 24 84 **Date Set:** 4/28/1978 **County:** Olmsted

Section: 13 **Township:** 108N **Range:** 14W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 5' east of centerline of N-S twp road and in line with fences E & W
County Survey Disk in 20" Maple NE 46.93'
County Survey Disk in NE side PP NW 62.60'
This corner is located by GPS measurement

Corner History:

6-1854 Gov't Notes: M.G. Karrick, Deputy Surveyor West on true line between sections 13 and 24. 40.00 chs. Set quarter section post in mound with trench and pits and charred stake and planted Osage Orange seeds N.E. and S.W. 80.00 chs. Section corner.

5-1877 Thomas Hunter (Book A P. 308 No. 302), County Surveyor, found a stone set in the center of the road by Henry Webster and Charley Brooker where the original corner stood. Set a temporary stake at the 1/16th East, set a boulder at the center 24, and set a stake and stone at the 1/16th South of the center 24. (old Field Book 5 P. 1) Hunter set a 6" x 10" x 18" stone at the 1/16th South.

8-1972 County Surveyor found the S. 1/4 Cor. 24 and the 1/16th North. Dug at the center 24 but did not find anything. Dug on line from the S. 1/4 Cor. 24 over the stone found at the 1/16th North and in line with the E-W fence at 1/4 Cor. 13-24 but did not find anything.

6-1-1976 County Surveyor dug again along the West side of the previous diggings to cover Hunter's full measure form the N.E. Cor. Sec. 24. Did not find anything. The 1/16th South comes in a deep cut in the road. Also dug again at the center 24 but did not find anything.

4-28-1978 County Surveyor set a C.I.M. over a 15" "T" bar on line from the S. 1/4 Cor. 24 over the center 24 (set this survey see cert.). RPs-CSD in 20" Maple NE 46.93. CSD in P.P. # 35047 West 85.85, corner falls 5' east of centerline of N-S twp road and in line fences E & W.

10-6-2005 County Surveyor found CIM down 0.3' in good condition.