Certificate of Location of Government Corner

ID#: 841405 **Description:** SEC COR 14 15 22 23 84 **Date Set:** 8/17/2005 **County:** Olmsted

Section: 14 **Township:** 108N **Range:** 14W **Monument Description:** Cast Iron Cap on telespar pipe

Reference Ties:

County Survey Disk in E side Oak N 20.30'
County Survey Disk in NW side Oak SE 19.29'
County Survey Disk in N side Oak ENE 17.30'
Post w/sign north 2'
This corner is located by GPS reference stations "Akerson B & C"

Corner History:

1854 Gov't Notes, M.Karrick; 80.0 Intersect N & S line 15 links north. West on true line between sections 14 & 23. 80.0 set section corner.

11-1872 T. Hunter Pg.211 No.219; Corner gone, but all bearing trees standing. Reset corner by b trees.

1916 Power Dam Survey: found stone.

5-1919 C.Armstrong Pg.308 B; Found stone monument as SW corner 14.

1941 J.Kerr Bk.23 A found limestone in pit with 3/4" pipe up 3' on west side. RPs- 8" white oak SSW 31.2, 10" white oak WSW 26.9, 18" hollow tree NE 35.6, 12" oak NE 51.0, 12" burr oak SSE 40.0 oak SW 50.0.

10-13-1961 County Surveyor found stone with 3/4" pipe beside it.

3-1973 County Surveyor found limestone with 3/4" pipe. RPs- 12" jack oak N41E 54 links 35.64 tree now 36.1 ENE to large dead oak, 16.3 east to blazed 12" white oak, 31.5 W to blazed 10" white oak, 27.2 S to blazed 16" white oak.

8-17-2005 County Surveyor found stone w/iron to the west. Took local ties and removed stone. Set 3 1/2' cast iron cap on telspar pipe up 0.8' at stone location.