Certificate of Location of Government Corner

ID#: 841804 **Description:** 1/4 SEC COR 18 19 84 **Date Set:** 5/20/70 **County:** Olmsted

Section: 18 **Township:** 108N **Range:** 14W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 3' west of N-S fence and 10' south of fence east
Original Gov't bearing tree (center of tree) N59° 30' E 58.08'
24" Elm in fence line (wrapped with wire) S 23° E 13.0'
This corner is located by GPS reference stations "Skeeter A & B"

Corner History:

1854 Gov't Notes, M.Karrick; 40.0 set temp 1/4 section post W 89° 51'E on true line between section 18 & 19. 38.0 set 1/4 section post. RPs- 10" white oak S23 E155, 8" burr oak N63 E88.

1913 4 surveyors by survey Pg.215; To relocate NE corner 19 west, found old post rotted off and lying on ground. Found origianl witness tree. Set sandstone with cross on top and 1/4 cut on side of stone. Drove large spike in weather hole on side of stone. Set new post marker . RP- S72°W 150.4' an elm tree.

4-1938 J.Kerr Bk.12 Pg.60; Found both corners. RPs to S 1/4 18-B.T. N56 1/2°E 57.6 20" burr oak, 8" elm S24 1/4°E 12.7, 20" elm S42°30' W 53.5.

1966 J. Kerr measured east from corner post.

5-20-1970 County Surveyor found stone. Set 3/4"x2' pipe in stake hole with beer cans, glass & black top below CIM. Set original stone down 6" and 0.7' north of CIM.

6-20-2001 County Surveyor found CIM at surface in good condition.