Certificate of Location of Government Corner

ID#: 842205 **Description:** SEC COR 21 22 27 28 84 **Date Set:** 4/17/74 **County:** Olmsted

Section: 22 **Township:** 108N **Range:** 14W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 4' east of fence north and 1' north of E-W fence
Sign on CP 4' WSW
This corner is located by GPS reference stations "Sattre A & B"

Corner History:

1854 Gov't Notes: M.G. Karrick, Deputy Surveyor North between sections 27 and 28. 80.00 chs. Set post for corner to sections 22-23-27-28. Erected mound with trench and pits and charred stake and planted Osage Orange seeds at each angle.

11-1894 William Fraser (P. 555 No. 512), County Surveyor, found remains of old stake and set 2 stones in its place. Set 1/16 stone North midway (1311.42') and on line.

3-1896 William Fraser (P. 592 No. 538) found corner.

1941 John Kerr (Book 23), County Surveyor, found corner on West side of corner post. Set stone 3" x 10" x 13".

1967 John Kerr found stone. Set C.I.M. over a 3/4" x 2' conduit. Found 1/16 stone North at 1311.0'. Set rod by corner.

4-17-1974 County Surveyor dug East of John Kerr's monument and found William Fraser's two stones (one on top of the other). This correct corner is 0.8' North and 4.4' East of John Kerr's C.I.M. Reset the C.I.M. and put a 1/2" rod on the North side of the bottom stone.

Note: This is a correction of a corner set by J. Kerr previously. These two correct stones were 0.8' North & 4.4' East of J. Kerr's corner location.

3-16-2001 Mn/DOT Survey Crew found monument in good condition.

12-5-2002 County Surveyor found CIM up 0.2' in good condition.