Certificate of Location of Government Corner

ID#: 842209 **Description:** SEC CEN 22 84 **Date Set:** 11/3/2006 **County:** Olmsted

Section: 22 **Township:** 108N **Range:** 14W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.
1" square pipe w/cap RLS #15809

Reference Ties:

County Survey Disk in NE side PP NW 67.76'
County Survey Disk in SE side PP #24403 NE 53.01'
This corner is located by GPS measurement and by GPS reference stations "Walker & Three Hole"

Corner History:

5-1941 John Kerr (Power Dam Survey), County Surveyor, found 1 1/2" iron bar. Measured south to 1/4 Cor. 22-27 and North to 1/4 Cor. 15-22. RPs- SW corner main school bldg WNWly 137.75, NE corner wood shed Nwly 250.49.

6-1967 John Kerr found iron shaft 18" below road surface and set a C.I.M. RPs- 20d on NW side pp NE 36.57, disc on SW side pp in school yard with head if 20D .1' south and lower NNW 76.35

8-1969 John Kerr removed C.I.M. for road grading. Set no additional ref. Points.

4-1974 County Surveyor found 5/8" x 6" rod in the bit. Surface. Dug with jackhammer and found another rod and the original 1 1/2" iron shaft. Set a 1" drill steel over the original shaft at the road surface. This corner lies 1.3' West of the North-South 1/4 line.

8-26-1976 McGhie & Betts found and used 1" drill steel.

1-17-1979 McGhie & Betts found and used 1" drill steel at center of section 22.

12-13-1982 McGhie & Betts found and used 1" drill steel.

10-1-1984 Yaggy Associates found and used 1" drill steel.

10-11-2005 County Surveyor found 1" drill steel, took local ties and removed.

10-13-2005 County Surveyor set 1" square pipe w/cap at surface from drill steel ties. CSD with concrete nail in NE side of PP #43219 NW 81.52' county highway department in SE side of PP #24403 NE 53.05'. Did not look for R/W monuments.

7-21-2006 County Surveyor removed 1" square pipe w/cap for overlay.

11-3-2006 County Surveyor set 1" square pipe w/cap from reference angle, updated ties.

5-7-2008 V. Fangman found and used pipe w/cap as center of section 22.