Certificate of Location of Government Corner

ID#: 842306 **Description:** 1/4 SEC COR 22 23 84 **Date Set:** 4/16/1974 **County:** Olmsted

Section: 23 **Township:** 108N **Range:** 14W **Monument Description:** Cast Iron Monument

Reference Ties:

County Survey Disk in N side 36" crippled Box Elder SW 23.70'
County Survey Disk in S side 15" Elm ESE 21.21'
Center 4" CP S 33.0' (leaning)
Post w/sign 2' south
This corner is located GPS reference stations "Finally A & B"

Corner History:

1854 Gov't Notes: M.G. Karrick, Deputy Surveyor North between sections 22 and 23. 40.00 chs. Set quarter section post. Br. Oak 10 in. S80°W 165 lks. Br. Oak 6 in. N10°E 185 lks. There are no known records after the Gov't survey on this corner location.

12-30-1886 T. Hunter (old field book #14 pg. 79) set stake M&L in plowed field.

4-16-1974 County Surveyor set a C.I.M. over a 1/2" rod at the intersection of the East-West 1/4 line of Sec. 22 and the East line of Sec. 22 by electronic traverse. RPS-Spike on E. side crippled Boxelder 10' W of S 22.12, Spike and Co. Surv. Disc So. Side 12" Elm S.W., 46.20', Center 4" corner post S 33.0'.

10-12-2005 County Surveyor found CIM in good condition down 0.4'. All ties in trees either removed or grown over. CSD with 60d spike in north side of 36" crippled box elder SW 23.70'. CSD with 60d spike in south side of 15" twin elm ESE 21.21'. Set sign and post 2.0' south.