Certificate of Location of Government Corner

ID#: 842505 **Description:** SEC COR 25 26 35 36 84 **Date Set:** 5/23/1967 **County:** Olmsted

Section: 25 **Township:** 108N **Range:** 14W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 2' east of N-S fence and 59' north of fence east
Nail and wood hub in E side 8" Burr Oak N 15.45'
1/2" pipe up 18" 1/2' west
Post w/sign 2' west
This corner is located by GPS reference stations "Schultz A & B"

Corner History:

1854 Gov't Notes, M.Karrick; 80.0 set post for section corner. RPs- 7" burr oak S61 W125, 6" burr oak N16 W93, 9" burr oak N36 E64, 6" burr oak S32 E125.

5-1877 T. Hunter Pg.308 No.302; Corner missing, but both witness trees standing. Reset corner.

6-1881 T. Hunter, unrecorded Pg.123 No.371; Set stone in place of stake.

5-1902 W.Fraser Pg.18B; found stone set by Hunter as 1/4 corner.

5-23-1967 J. Kerr found limestone as recorded set by Thos. Hunter in 1881. Set CIM over 1"x12" pipe. RPs-Nail and wood hub nailed to North side twisted Burr Oak tree of 20" diameter East 52.9'. Nail and wood hub nailed to East side 8" Burr Oak tree, North 15.45'. Farm fence line running East South 59.0'.

9-26-2005 County Surveyor found CIM in good condition down 0.1' surrounded by stone. All ties still there except for nail in twisted Burr Oak. Set sign and post 2.0' west in N-S fence.