Certificate of Location of Government Corner

ID#: 842605 **Description:** SEC COR 26 27 34 35 84 **Date Set:** 7/27/2004 **County:** Olmsted

Section: 26 **Township:** 108N **Range:** 14W **Monument Description:** 1" square pipe w/cap RLS #15809

Reference Ties:

The corner falls 3' south of centerline of twp road west and in centerline of N-S twp road
Steel fence CP SW 48.60'
County Survey Disk in SW side PP NW 107.58'
Top center 6" sq tele box SW 62.82'
Disc in PP SE 46.28'
Spud in TP SW 58.20'
Top TCM box E 36.31'
Spud in TP S SW 61.40'
This corner is located by GPS measurement

Corner History:

1854 Gov't notes, M.Karrick; 80.0 set post for corner to section 26-27-34-35. Erected mound with trench, pits, charred stake, and planted osage orange seeds at each angle.

Records not positive; Unrecorded survey 6-1881 may have used corner. Limestone used by county highway department in line fence east has proved in various ways to be true corner. Accepted by Farmer Fredricks as true corner.

6-1934 J.Kerr on digging in area in presents of farmer Fredricks found whar all conserned considered as corner. Set limestone, later found as corner.

9-14-1963 J.Kerr, set CIM in place of corner. RPs- Disc in pp SE 46.28, spud in tele pole SW 58.2, spud in tele pole SSW 61.4, steel corner fence post SW 48.6.

8-28-1974 County Surveyor set CIM over original CIM and took new reference.

7-21-2004 County Surveyor found CIM down 1.16' with head busted off in good condition. Took local ties and filled back in with blacktop.

7-27-2004 County Surveyor set 1" square pipe w/cap at surface from local ties.

9-26-2005 County Surveyor found 1" square pipe w/cap in good condition at surface.