Certificate of Location of Government Corner

ID#: 842706 **Description:** 1/4 SEC COR 27 28 84 **Date Set:** 6/1/1981 **County:** Olmsted

Section: 27 **Township:** 108N **Range:** 14W **Monument Description:** Contact County Surveyor for more information
Witness Corner: 1" square pipe w/cap RLS #8952 is 590.08' east of corner location

Reference Ties:

Witness Corner:
Yellow well cap "WISA" NNE 83.2'
Yellow well cap "WISB" NW 41.3'
Post w/sign 2' east
This corner is located by GPS measurement

Corner History:

1854 Gov't Notes, M.Karrick; 40.0 set 1/4 section post in mound with trench, pits, charred stake, and osage orange seeds NE & SW.

6-1884 T. Hunter Pg.390 No.381; Found stone.

3-1896 W.Fraser Pg.592 No.538; Couldn't find corner. Set temp point by line from center 27 over 1/16 corner west & doublind measure.

9-1969 J.Kerr set 8x8x30 conc. Monument with metal cap with cross. Set steel post by corner.

6-1981 County Surveyor set witness corner (1" square pipe w/cap) at location of W. Fraser stone 590.08' East of 1/4 cor 27-28.

3-16-2001 Mn/DOT Survey Crew found nothing at corner location. Found 1" square pipe w/cap at witness corner location 590.08' East.

12-3-2002 County Surveyor found witness corner at surface in good condition.