Certificate of Location of Government Corner

ID#: 842905 **Description:** SEC COR 29 30 31 32 84 **Date Set:** 5/12/75 **County:** Olmsted

Section: 29 **Township:** 108N **Range:** 14W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls in centerline of E-W twp road and in line with fence south
Punch mark in north bolt on N end large CMP ENE 63.35'
Punch mark in south bolt on S end large CMP ESE 63.84'
County Survey Disk in W side CP S 38.42'
This corner is located by GPS measurement

Corner History:

10-1853 Gov't Notes: W.B. Yerby, Deputy Surveyor North between sections 31 and 32. 80.00 chs. Set corner post to sections 29-30-31-32. Built mound of earth and sod. Deposited charcoal. Made trench and pits and planted Osage Orange seed N.W. and S.E.

5-1873 Thomas Hunter (P. 224 No. 227), County Surveyor, found boulder stone set by and avered by Mr. Brachenridge, a pioneer landowner, as set where original corner stood.

1913 David Williams (P. 217 Book B), County Surveyor, makes no mention of corner here so bridge likely in place.

7-1966 John Kerr, County Surveyor, found old cross cut in bridge as corner from earlier work on perpetuating the corner location and renewed mark.

5-1972 County Surveyor referenced corner before road and bridge construction.

5-12-1975 County Surveyor road regraded and the bridge destroyed. Reset a C.I.M. over a 3/4" x 17" rod from the transit ties. RPs-63.84 Punch mark in most Northerly bolt intop N. end of large C.M.P. 63.35 Punch mark in most Southerly bolt on S. end of large C.M.P. 38.42 Co. Surv disc on top W. side corner post. 1/2" x 30" rod on transit line 1/2" x 30" rod. 80' 180'.

3-7-2001 Mn/DOT Survey Crew found corner in good condition down 0.2'

4-2-2001 County Surveyor found CIM down 0.2' in good condition.