Certificate of Location of Government Corner

ID#: 842906 **Description:** 1/4 SEC COR 29 30 84 **Date Set:** 9/21/72 **County:** Olmsted

Section: 29 **Township:** 108N **Range:** 14W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 17 1/2' south of centerline of E-W twp road, 17' east of centerline of twp road north and 22' east of fence south
Bottle cap in SE side PP #36723 ENE 135.1'
Bottle cap in SW side TP NW 81.2'
Conc. Nail in NW side CP SW 26.77'
This corner is located by GPS measurement

Corner History:

1854 Gov't Notes; 40.0 set 1/4 section post in mound with trench, pits, charred stake, & osage orange seeds NE & SW.

5-1899 R. Fraser Bk. A pg. 642. Found the boulder in the center of the road with a stake by the stone. Dug with tractor twice and finally found two stones set vertically over a wooden stake. Drove a 1/2" by 3' rod in the stake hole and set a C.I.M.

1966 J.Kerr meas. NE 19 to 1/4 31-32. Set 120D on south edge of traveled road surface. Set at 2640' from 120D set at 19-20-29-30 this total from NE 19 7894.7. This 120D comes on S edge road and 25.5' SW to corner fence post.

9-21-1972 County Surveyor found the original stake beside two stones. Set 1/2"x3' rod thru stake with stone and glass by rod and CIM over the mess. RPs-Bottle cap on the S.E. side of P.P. # 36723 E.N.E. 135.1'. Bottle cap on the S.W. side of tele. Pole N.W. 81.2'. Conc. Nail on the N.W. side of corner post S.W. 26.77'. Line of fence running South W. 22'. The corner lies 6' S. of the South edge of the road and 17' East of the center of the road running North.

4-1986 Tom Ferguson found CIM and tied it to Mn/DOT horz. Control station "Prokasky" WNW 12.75'.

3-6-2001 Mn/DOT Survey Crew found monument in good condition.

4-2-2001 County Surveyor found CIM down 0.5' in good condition.