Certificate of Location of Government Corner

ID#: 843106 **Description:** W 1/4 SEC COR 31 84 **Date Set:** 8/1/1964 **County:** Olmsted

Section: 31 **Township:** 108N **Range:** 14W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 1' west of centerline of N-S twp road
Cross in S end damaged culv. Headwall E 20.0'
Cross in N end culv. Headwall NE 30.0'
60d spike in 15" Pine NE 42.37'
County highway disk in PP ENE 51.55'
County highway disk in PP SSW 33.0'
This corner is located by GPS measurement

Corner History:

5-1870 Perry Pg.112 No.149; Found stone as corner. Tested SW bearing tree (6" tree now 14"). North set quarry stone 26" long at 20.90.

6-1899 Robert Fraser Pg.643 No.579 1/2; Found limestone 3x6x36 in west rut of road. Avered by Mr. Keefe to have been there for a long time. Also, know by Mr. Palmer to be true corner.

8-1964 County Surveyor corner 1 1/4"x30" pipe in glass and rock replacing corner found in surveys of private surveyors. Set CIM over 1"x14" pipe. RPs-Cross in S end damaged culv. Headwall 20.0', Cross in north end culv. Headwall NE 30.0', 60D in 15" pine NE 42.37', Disc in pp of trans. Line ENE 51.55', Disc in pp SSW 33.0', Corner lies in line row of trees south of farm drive.

1-22-2003 County Surveyor found Cast Iron Monument in good condition down 1'.