Certificate of Location of Government Corner

ID#: 843206 **Description:** 1/4 SEC COR 31 32 84 **Date Set:** 4/18/2006 **County:** Olmsted

Section: 32 **Township:** 108N **Range:** 14W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls 1' south of CP to fences north and west
County Survey Disk in S side 15" Box Elder leaning NE 10.85'
County Survey Disk in W side 6" Aspen SE 9.01'
Post w/sign 2' north
This corner is located by GPS reference stations "Ardie A & B"

Corner History:

5-1870 R. Perry Pg.112 No.149; found stone in old mound & pits all four directions.

5-1873 T. Hunter Pg.224 No.227; Found boulder stone set in center of road.

7-1902 R.Fraser Pg.50 No.10; Found boulder from previous survey.

1913 D.Williams & others Pg.217B; Found large boulder and old stake. Accepted as corner.

7-19-1966 J. Kerr found boulder 24" x 18" x 12" with large stake on South side. Removed large stone and set 1/2"x2' rod deep. Set CIM over both stone & rod. RPs- 120D on E side 6" pine SE 15.0, disc in cresote corner post of N-S fence E 20.7, disc in tele pole W 22.6, corner lies 1' south of corner post in line of present fence north & west. Set 1/2"x3' rod up 5" north 2599 or 33' south of section corner.

3-7-2001 Mn/DOT Survey Crew found monument in good condition.

1-21-2003 County Surveyor found CIM in good condition leaning slightly NE up 0.1'. Monument falls inline w/fence running North and 1.0' North of fence line running West. Set sign & post 1.7' North of monument.

4-18-2006 County Surveyor found CIM leaning NE up 0.1', took local ties removed. Found stone down 1.9', took local ties to center dimple removed. Did not find 1/2" iron rod. Set 6' telspar pipe w/CIC from ties taken from CIM up 0.3'. CSD w/concrete nail in south side of 15" Box Elder leaning north, E 10.85'. CSD w/concrete nail in west side of 6" Aspen tree SE 9.01'. All other ties gone except for nail and disc in corner post east. Could not take tie because of leaning Box Elder. Set sign and post 2.0' north.