Certificate of Location of Government Corner

ID#: 843606 **Description:** 1/4 SEC COR 35 36 84 **Date Set:** 10/31/1990 **County:** Olmsted

Section: 36 **Township:** 108N **Range:** 14W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls 1/2' east of face of CP to fences west and south
County Survey Disk in 4" Cherry tree NW 14.72'
County Survey Disk in 6" Cherry tree ENE 27.61'
County Survey Disk in CP NE 0.91'
This corner is located by GPS reference stations "Hidden Key A & B"

Corner History:

6-1854 Gov't Notes, Michael Karrick, Deputy Surveyor North between sections 35 and 36 40.00 chs. Set quarter section post 12" bur oak S82°W 475 lks. 8" bur oak N61°E 258 lks.

1916 Power dam survey used fence corner measured south 2605.6', measured north 2661.0'.

1969 McGhie & Betts used corner post set iron rod at center of section 36.

10-5-1990 County Surveyor dug around corner post to fences south and west found nothing.

10-31-1990 County Surveyor set telspar pipe with cast iron cap to match McGhie & Betts quarterline from east in section 36. Monument is 0.5' east of face of corner post. RPs-Monument is 1/2' east of face of corner post to fences west and south. Spike and C.S.D. in 4" cherry tree NW 14.72', Spike and C.S.D. in 6" cherry tree ENE 27.61', C.S.D. in corner post NE 0.91'.

10-3-2005 County Surveyor found telspar pipe w/CIC in good condition up 0.6'.