Certificate of Location of Government Corner

ID#: 850105 **Description:** SEC COR 1 2 11 12 85 **Date Set:** 7/2/64 **County:** Olmsted

Section: 01 **Township:** 108N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 9' ESE of CP
This corner is located by GPS measurement

Corner History:

1854 Gov't Notes, John Cushing; 80.0 set post corner of section 1-2-11-12 with raised mound, trench, and charred stake.

1-1897 W. Fraser Pg.604 No.549; Found long boulder as corner set as corner for many years past, everyone interested was satisfied. Measured west and south.

5-1898 W. Fraser Pg.629 N0.569; Found corner Pg.604, 16 east set iron stake

6-1902 Charles Armstrong Pg.54B; Found stone with iron rod beside it. Measured north.

1919 McGhie & Betts, Blue Book indicates stone found in treeline of gateway on S side of gate.

10-1960 J.Kerr Bk.82 Pg.11; Found Corner, set pipe among stones and measured east.

7-2-1964 County Surveyor set CIM over 1"x10" pipe.

7-6-2001 County Surveyor found CIM in good condition. Set sign in C.P.

4-12-2011 Mike Hendrickson, MNDOT, found cast iron monument down 0.5'. Left monument as found. Measured the following reference ties:
County survey disk in south side of corner fence post - 6.5' WNW
Nail and disk in SE side of brace post - 0.85' Northeast