Certificate of Location of Government Corner

ID#: 850306 **Description:** 1/4 SEC COR 3 4 85 **Date Set:** 10/1/1985 **County:** Olmsted

Section: 03 **Township:** 108N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 1' south of E-W fence and 117' east of drainage ditch
County Survey Disk in N side RR tie CP ESE 37.76'
County Survey Disk in W side NSP PP #40 NNW 70.96'
SW corner porch foundation (concrete block) NE 77.17'
This corner is located by GPS measurement

Corner History:

6-12-1854 Gov't Notes: John Cushing, Deputy Surveyor, north on true line between sections 3 & 4. 80.60 chs. Intersect Standard Parallel No. 2 11 chs. 4 links. East of 1/4 post on south line section 33 in Twp. 109-15 and set post for corner to section 3-4. Erected mound, trench, pits, and charred stake per instructions.

9-19-1985 County Surveyor found limestone, but no stake. Drove 3/4" rerod at location of stone.

10-1-1985 County Surveyor set CIM over the iron previously set at stone location. Corner in farm driveway and 5 1/2" south of the centerline of the main road running west and 6 1/2 west of centerline main road running south and 4' north of fence running east. RPs-CSD in N side RR tie corner post ESE 37.76', CSD in west side NSP PP #40 NNW 70.96', SW corner porch foundation (concrete block) NE 77.17.

7-6-2001 County Surveyor found CIM in good condition.