Certificate of Location of Government Corner

ID#: 850405 **Description:** SEC COR 4 5 8 9 85 **Date Set:** 5/21/75 **County:** Olmsted

Section: 04 **Township:** 108N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls in centerline of E-W twp road, in line with fence north and 33 1/2' east of centerline of driveway south
This corner is located by GPS measurement

Corner History:

1854 Gov't Notes: Cushing, Deputy Surveyor; North between sections 8 & 9. 80.0 chs. Set corner to sections 4-5-8-9. Erected mound with trench as per instructions. Drove charred stake.

5-1900 Robert Fraser (Pg.673 No.598), County Surveyor found boulder claimed by a Mr. Randle to have been set by Mr. Hamilton, a surveyor. Also found a limestone 2"x6"x18" with rotted stake by its side in center of road which Mr. Gritzs avers Mr. Page, a surveyor, set 20 years before where he found original stake. Limestone 7 links south and 4 links west of boulder. (Fraser doesn't say which he used)

9-1966 J. Kerr measured east from CIM set at 1/4 5-8 where original stone was found, set 120d 2' north of south edge of rock surface in line of east side of field drive south at 2640'. Land on north side common land no fence now.

5-21-1975 County Surveyor found 2"x6"x18" limestone and stake 3' deep beneath a boulder. Also found 3/4" rod with steel tractor wheel lugs ±1/2' east of limestone. Dug north and east to see if Fraser's boulder was still in place, but found nothing. Removed rod found and set the 4 steel tractor wheel lugs around the stone. Set CIM over 3/4"x8" rod over stone.

2-27-2001 County Surveyor found CIM down 0.6' in good condition.