Certificate of Location of Government Corner

ID#: 850506 **Description:** 1/4 SEC COR 5 6 85 **Date Set:** 5/3/66 **County:** Olmsted

Section: 05 **Township:** 108N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 1' north of fence west and 1 1/2' west of fence north
Nail & hub in twin Ash S 22.5'
This corner is located by GPS measurment

Corner History:

1854 Gov't Notes: Cushing, Deputy Surveyor; North between section 5 & 6.
40.0 set quarter section post. RPs- 6" cherry N39W 6 links, 18" white oak S42E 14 Links.

9-1882 T. Hunter Pg.379 No.370; Found stake claimed set by Noble. Ano bearing trees left. Left corner as found.

5-1889 Thomas Fraser Pg.428 No.416; Found stake Pg.379 and accepted as found. 16 east set stake, 16 north set stake.

6-1901 W. Fraser Pg.6 B; Found stake by side of corner post. Set stone in its place. 16 north found stake, set stone at 19.96, north found stake, set stone at 14.27, west set stone at 14.75.

5-1966 J. Kerr; Found recorded stone by corner post. Set CIM over 5/8"x18" rod.

9-15-1976 County Surveyor, 1/16 north, corner comes on south edge of ditch, dug and found nothing. Measured from 1/4 cor. 5-6 found.

3-26-2001 County Surveyor found CIM down 0.4' in good condition.