Certificate of Location of Government Corner

ID#: 850507 **Description:** N SEC COR 5 6 85 **Date Set:** 7/14/65 **County:** Olmsted

Section: 05 **Township:** 108N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 2' north of centerline of E-W twp road and 78' west of centerline of road north
Nail & disc in PP WSW 151.9'
Nail & disc in PP ESE 98.03'
Corner of porch 5' up slope measure NNE 88.0'
This corner is located by GPS measurement

Corner History:

9-1882 T. Hunter Pg.379 No.370; Corner gone. Found stake used in sub-dividing S 31 north. By this line and measure set NE corner 6.

5-1889 Thomas Fraser Pg.428 No.416; Found stake set by Hunter Pg.379 and stone by its side. Tested and accepted as correct as found. 16 east set stake, 16 south set stake.

6-1901 W.Fraser Pg.6b; Found iron stake driven as corner. South found iron stake, west found iron stake.

6-1929 J. Kerr Pg.424B; Found iron stake, set pipe over it with boulder under lilac bushes 18.9' as witness.(gone)

7-1965 J. Kerr set CIM over railroad spike. RPs- Disc in pp ESE 98.05'(98.03), disc in pp WSW 151.8'(151.9), SE corner porch addition of house E of N slope 88.0'.

9-10-1976 County Surveyor found CIM 6" deep in centerline road. Took reference points.

3-22-2001 County survey crew found CIM down 0.8' in good condition.