Certificate of Location of Government Corner

ID#: 850606 **Description:** W 1/4 SEC COR 6 85 **Date Set:** 5/3/66 **County:** Olmsted

Section: 06 **Township:** 108N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 1 1/2' west of N-S fence and in line with fence east
Center of 30" Maple SE 32.5'
Center of 30" Basswood NNW 38.0'
Post w/sign 2' north
This corner is located by GPS reference stations "Koop A & B"

Corner History:

1853 Gov't Notes: Ball, Deputy Surveyor; North between sections 1 & 6. 40.0 set quarter section post. RPs-12" lind S23E40 links, 14" elm N35W 68 links, 14" aspen 40.22'

9-1882 Hunter Pg.379 No.370; Found badly rotted stake and 2 witness trees standing, set new stake beside old stake (set new B.O. stake properly marked). East gov't record 39.83 actual 39.50 set stake on line at 19.66.

5-1900 R. Fraser Pg.672 No.597; Found stumps of bearing trees and old stake remains. Drove new burr oak stake and took 2 bearing trees: 10" elm N 14 1/2W 42 links and 10" burr oak S11°W 9 links.

6-1901 W. Fraser Bk.B: Found stake and stone as corner. 16 east set stake at 19.66, north set 4 stakes for woodlots acerages.

5-1924 J.Kerr B. 7 Pg.5 & 6; Found bearing trees Pg.672 and shattered limestone by corner post. Mr. Deveny avers to be true corner, left as is. 16 east run line to center 6 and set iron stake at 1283.5, total 2609.6, same bearing trees as Pg.672.

5-1966 J.Kerr; Stone gone. Set CIM over 3/8"x3' rod in limestone.

3-23-2005 County Surveyor found CIM down 0.5' in good condition. Set post w/sign 2' north.