Certificate of Location of Government Corner

ID#: 850706 **Description:** W 1/4 SEC COR 7 85 **Date Set:** 3/23/2005 **County:** Olmsted

Section: 07 **Township:** 108N **Range:** 15W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

County Survey Disk in railrod tie post E 118.35'
This corner is located by GPS measurement

Corner History:

1853 Gov't Notes: John Ball, Deputy Surveyor, North between sections 7 & 12. 40.0 chs. Set a quarter section post. RPs- 6" white oak N26°E 21 links, 6" black oak N45°W 1o links.

9-10-1976 County Surveyor doubled the line and measure from the west section corner 7-18 over a stone found at the 1/16 north (recorded by Cap Maxon, a county surveyor in Dodge County) and dug for the corner. Found an 8"x8"x15" boulder coming to a point on top 2' north of the base of a large old post in the E-W fence line. The corner came 1.94' south and 1.30' east of the computed location. Set a CIM over a 1/2"x2' rod as the corner and set the boulder on the south side of the CIM.

3-15-1985 County Surveyor, all ties and fence E-W gone in woods grubbing. New RP-CSD in railroad tie post east 118.42'. Set survey marker sign & post 0.5' north of CIM.

3-23-2005 County Surveyor found 1/2" iron rod down 1.2'. CIM and post w/sign both gone. Set 5' telspar w/CIC down 1.2' over iron rod. CSD in north side of railrod tie set in fence east 118.35'