Certificate of Location of Government Corner

ID#: 850804 **Description:** 1/4 SEC COR 8 17 85 **Date Set:** 10/20/81 **County:** Olmsted

Section: 08 **Township:** 108N **Range:** 15W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls 2 1/2' west of N-S fence and in line with fence east
County Survey Disk in SE side 20" Burr Oak NE 8.75'
Top corner of angle iron CP NNE 6.21'
This corner is located by GPS measurement

Corner History:

1854 Gov't Notes: John Cushing, Deputy Surveyor, West on true course. 40.0 chs. Set 1/4 section post from which an 6" aspen B. S89 °E16 links and 7" burr oak B. N81 °W 11 links. 80.0 chs. Section corner.

6-1873 & 12 1873 Thomas Hunter, County Surveyor, (Bk.A Pg.234 No.237 and Old Fieldbook 3 Pg.35-36 and 59-62) Found old 1/4 post on ground and hole where it stood with small piece of stake in hole. Found NW witness tree,but other gone. Tested and found distance correct. Reset 1/4 post in hole and used this corner to set 1/16 south.

2 & 3-1892 Thomas Fraser, County Surveyor, (Bk.A Pg.471 No.452 and Old Fieldbook 8 Pg.11; Didn't find anything at corner.

10-1981 County Surveyor found remains of Gov't corner as found by Hunter in 1873. Set CIC as corner. Took measurements.

3-19-2001 County Surveyor found cast iron cap on telspar pipe at surface in good condition.