Certificate of Location of Government Corner

ID#: 850805 **Description:** SEC COR 7 8 17 18 85 **Date Set:** 5/21/73 **County:** Olmsted

Section: 08 **Township:** 108N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 1 1/2' west of centerline of CR 113, 111 1/2' south of centerline of field drive east and in line with fence west
Spike & disc in 24" Oak W 46.07'
County Survey Disk in PP #35 46.48'
This corner is located by GPS measurement

Corner History:

1854 Gov't Notes: John Cushing, Deputy Surveyor; 80.0 set corner post of section 7-8-17-18. RPs- 5" burr oak B N68W 19 links, 4" cherry B N1E 19 links, 6" aspen B S85E 34 links, 5" burr oak B 20W 49 links

12-1873 T. Hunter Pg.235 No.237; Found stone in center road, tested witness trees, all but one still standing. 16 south set stake M & L 20.0. 16 center NW 1/4 17 set stake M & L 19.96 on E-W 1/16 line.

3-1892 Thomas Fraser Pg.471 No.452; Couldn't find corner and didn't set it.

7-1893 W Fraser Pg.524 No.489; Found stone center road and remains of old stake Pg.235 and stumps of NW & SW bearing trees. Drove iron stake in place of old stake with stones on 2 sides of iron rod.

1939 county highway department Bk.100 Pg.3; Boulder stone with stake on top. RPs- spike in SW corner barn NE 54.2', spike in maple SW 66.7', spike in elm SE 93.7'. Assumed corner, measured south 5273.75 BK.191 5268.1 Bk.100. RPs- disc in 12" pine west 36.7, disc in 12" elm SE 94.4.

10-22-1971 County Surveyor found iron shaft and L stones on N & S sides. Set CIM over corner as found.

5-21-1973 county highway department set CIM after grading 4" below top of rock. RP's: Spike and disc in 24" tree W 46.07' top center tele cable marker post SSE 134.42'. Spike and disc in PP SE 47.41'. Spike and disc in 24" tree SE 94.40'

3-27-2001 County Surveyor found CIM down 1' in good condition.