Certificate of Location of Government Corner

ID#: 850905 **Description:** SEC COR 8 9 16 17 85 **Date Set:** 10/22/75 **County:** Olmsted

Section: 09 **Township:** 108N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 14' north of centerline of E-W driveway and in line with fence north
County Survey Disk in W side 12" Choke Cherry S 33.75'
County Survey Disk in W side CP N 1.22'
This corner is located by GPS measurement

Corner History:

8-1854 Gov't Notes: John Cushing, Deputy Surveyor; North between sections 16 & 17. 80.0 chs. Set corner post to sections 8-9-16-17. RPs- 5" jack oak S69E 22 links, 6" jack oak S15W 61 links, 8" jack oak N46W 29 links, 6" jack oak N67E 55 links.

12-1894 William Fraser (Pg.556 No.513), County Surveyor reset corner from the SW bearing tree and the stump of the NW bearing tree with stake. Set stone by stake.

10-4-1971 County Surveyor dug and found 3"x5"x12"x19" limestone 1 1/2' south of the corner post to fences north and west.

10-22-1975 County Surveyor dug out limestone found in 1971 and set CIM over 3/4"x24"rod as corner. Set stone on west side of CIM and angle iron on east side up 2'.

3-19-2001 County Surveyor found CIM down 0.4' in good condition.