Certificate of Location of Government Corner

ID#: 851109 **Description:** SEC CEN 11 85 **Date Set:** 1/1/1971 **County:** Olmsted

Section: 11 **Township:** 108N **Range:** 15W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.
1/2" rod

Reference Ties:

The corner falls 6 1/2' south of E-W fence and 16' east of fence north
Steel post 0.6' South
This corner is located by GPS reference stations "Grabau A & B"

Corner History:

1-28-1897 W. Fraser (P.604 No.549) located corner by true inters lines. Drove iron stake as corner, took B tree 8" rock elm N 12-1/2°E 12 links, Bass wood stump S 64-1/2° E 23 links. 16 south found stake set in previous survey. Meas south 39.80'. 16 east drove stake M&L 20.52-1/2 1354.65'.

1971 Tom Ferguson set corner, probably iron rod.

3-23-1972 McGhie & Betts found and used 1/2" rerod.

8-1-1981 County Surveyor found 1/2" rod.

8-21-1984 Vince Fangman found 1/2" rod set steel post near corner. RP's 60d spike in 30" dead elm N 7.00'. 60d spike in 48" Elm stump ENE 16.42'. Vince computed center came .12' N and.43' E.

8-22-1985 V. Fangman found and used 1/2" rod.

12-12-2002 County Surveyor found 1/2" rerod at surface in good condition.

4-12-2011 Mike Hendrickson, MNDOT, found 1/2" rerod. Left monument as found. Measured the following reference ties:
Nail and disk up 2' in east side of 6" boxelder tree - 6.5' North
Nail and Disk up 1' in southeast side of 12" boxelder tree - 10.9' northeast