Certificate of Location of Government Corner

ID#: 851204 **Description:** 1/4 SEC COR 12 13 85 **Date Set:** 4/23/1964 **County:** Olmsted

Section: 12 **Township:** 108N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 28' south of centerline of twp road west, 23 1/2' west of centerline of twp road south and 15' NE of centerline of twp road on curve
The monument is down 0.7'
Spike w/punch mark in PP SW 58.49'
This corner is located by GPS measurement

Corner History:

6-12-1854 Gov't Notes Cushing, Deputy Surveyor; West on true line between 12 & 13. 40.0 set quarter section post. Raised mound with trench and drove charred stake. 80.0 section corner.

5-6-1898 W. Fraser (Pg.629 No.569) Corner came in field. Set marked stake M & L 39.76 (2624.16') . RP- 4" burr oak N60 3/4°E 75 1/2 links. 16 west drove stake, 16 north set stake M & L, 16 center SW 1/4 12 set stake M & L.

4-15-1903 Charles Armstrong (Book B, Page 49) corner stake on plat. Measured west. 16 east stake M & L, 16 south stone.

6-7-1960 J. Kerr (B81 P23) Run south line and set iron pipe M & L, RP- Spike in pp SW 58.5'. 16 west found iron stake pg.629 at 1312 M & L. Set iron rod M & L 2624. 16 north set 1/2" rod M & L 1306.25'. RPs- 20" ash S61°45W 110', 18" elm N31°05W 162.5'.

4-23-1964 J. Kerr set CIM over limestone and pipe.

6-7-2001 County Survey Crew found CIM down 0.8' in good condition. Located its position using GPS.

1-27-2003 Mn/DOT Survey Crew found monument in good condition.

5-10-2010 County Survey Crew found CIM down 0.7' in good condition.

6-1-2011 Travis Dunn, MNDOT Survey Crew, set additional ties as follows:
3/4" iron pin, 69.79, Azimuth 175 degrees 28 minutes 15 seconds
3/4" iron pin, 43.25, Azimuth 145 degrees 17 minutes 24 seconds
3/4" iron pin, 60.59, Azimuth 303 degrees 21 minutes 29 seconds