Certificate of Location of Government Corner

ID#: 851205 **Description:** SEC COR 11 12 13 14 85 **Date Set:** 7/2/64 **County:** Olmsted

Section: 12 **Township:** 108N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 9 1/2' WNW of CP to electric fences S & E
Center 14" Burr Oak WSW 32.6'
Post w/sign 2' south
This corner is located by GPS reference stations "Gathje A & B"

Corner History:

1854 Cushing, Deputy Surveyor; North between sections 13 & 14. 80.0 set section corner. Made raised mound with trench, and charred stake.

12-1894 W. Fraser Pg.556 No.513; Found stone set by Packard & Button, placed when mound and pits were plain. 16 west set stake.

1-1897 W. Farser Pg.604 No.547; Found stone pg. 556. 16 north drove stake and measured west.

5-1898 W. Fraser Pg.629 No.569; Found stone pg.604. 16 east drove iron stake, 16 north found stake set pg.604.

4-1903 Charles Armstrong Pg.49B; Found stone, 16 south set stake.

6-1960 J. Kerr Bk.81 Pg.23; Found stone and 1/16 iron east set S 1/4 12 all 1312', stone real large triangular boulder by corner post.

7-1964 County Surveyor set CIM over 1"x11" pipe with original boulder up 18" north of CIM.

12-9-1996 County Surveyor, on notice of adjoining property owner Mr. Suther, he said his neighbor had bulldozed out the corner. We found CIM 6" deep. The stone that guarded it and the corner post are gone. The oak tree tie is still there WSW 32.6' by J.K to center oak. Set post and sign 1' north of CIM. Corner falls in line of old bulk head and 1' north of electric fence line running east. The corner post to the electric fence running east and south is ESE 9 1/2'.

6-7-2001 County Surveyor found CIM down 0.5' in good condition.