Certificate of Location of Government Corner

ID#: 851306 **Description:** 1/4 SEC COR 13 14 85 **Date Set:** 11/5/77 **County:** Olmsted

Section: 13 **Township:** 108N **Range:** 15W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls on NE side of CP to fences N-S-E-W
Post w/sign 2' west
The corner is located by GPS reference stations "Prokasky C & D"

Corner History:

1854 Gov't Notes: Cushing, Deputy Surveyor. North between sections 13 & 14. 40.0 chs. Set quarter section post. RPs- 4" burr oak N67°W 30 links, 4" cherry S26°W 50 links.

1-1892 Thomas Fraser, (Pg. 468 No. 450) County surveyor measured south 1 1/2 miles from this center to set the SW corner 13 N-S at 1/3 the distance (39.78 & 2/3 chs.).

4-1903 Charles Armstrong (Pg.49B-plat only) shows a stone at the corner midway between the section corners (at 39.85 chs.).

11-2-1977 County Surveyor dug on the NE side of the corner post to the fences N-S-E-W. Found a 8"x11"x28" boulder on the NE side of the corner post with a steel fence post driven 4' deep .35 north of the stone. Removed the steel fence post and set a 1/2"x2' rod at its location.

11-5-1977 County Surveyor set a CIC on a square pipe at the location of the 1/2" set 11-2-1977. The corner came on the line from the corner post at the E 1/4 corner 13 over the center 13 (found).

9-13-2005 County Surveyor found telspar w/CIC in good condition down 0.1'. Set sign and post 2.0' west.